



Model 600 Tree Branch Chipper

1-2 T/H CAPACITY | BRANCH SPECIAL

APPLICATIONS

- Branch special chipping
- Forestry thinning
- Orchard heavy pruning
- Roadside tree maintenance
- Branch collection point

KEY FEATURES

- 18HP diesel engine, high torque
- Branch special design, no jam
- Towable chassis, easy transfer
- Heavy duty frame, durable
- High efficiency for fresh branches



TECHNICAL SPECIFICATIONS

Parameter	Metric	Imperial
GENERAL		
Capacity	1-2 T/H	1.1-2.2 ST/H
Max Processing Diameter	120 mm	4.7 inches
Overall Dimensions (L×W×H)	1900×850×1450 mm	74.8×33.5×57.1 inches
Operating Weight	350 kg	772 lbs
Output Size	10-30 mm	0.4-1.2 inches
POWER UNIT		
Engine Type	ingle cylinder 4-stroke air-cooled diesel engine	
Rated Power	13.2 kW	18 HP
Engine Speed	3600 RPM	
Start Method	Electric start + recoil start	
Fuel Tank Capacity	5.5 L	1.5 US gal
CHIPPING SYSTEM		
Cutter Disc Speed	2200 RPM	
Blade Configuration	3pcs hardened alloy blades	
Drive System	Double V-belt drive	



TECHNICAL SPECIFICATIONS

Parameter	Metric	Imperial
FEED SYSTEM		
Feed Method	Manual feed	
Hopper Design	Branch special wide hopper	
DISCHARGE SYSTEM		
Discharge Chute	360° rotatable discharge	
Discharge Height	1800 mm	70.9 inches
UNDERCARRIAGE		
Travel Method	Towable wheeled	
Tire Specification	2pcs 14 inch off-road tires	
Support Leg	Front foldable support leg	
Trailer Hitch	Standard trailer hitch	

SAFETY FEATURES

- Emergency stop button
- Feed hopper anti-rebound baffle
- Reinforced cutting chamber guard
- Double belt guard
- Engine low oil protection

END PRODUCT & APPLICATIONS



Product Showcase



Typical Applications