



Model 6158 Industrial Branch Chipper

3-5 T/H CAPACITY | INDUSTRIAL TOWABLE

APPLICATIONS

- Professional tree service
- Large scale landscaping
- Municipal forestry
- Disaster relief branch cleaning
- Large wood chip sales

KEY FEATURES

- 35HP diesel engine
- Single axle towable chassis
- Hydraulic auto feed
- 3-5T/H industrial capacity
- 360° rotatable discharge chute



TECHNICAL SPECIFICATIONS

Parameter	Metric	Imperial
GENERAL		
Capacity	3-5 T/H	3.3-5.5 ST/H
Max Processing Diameter	200 mm	7.9 inches
Overall Dimensions (L×W×H)	3500×1600×2200 mm	137.8×63.0×86.6 inches
Operating Weight	1500 kg	3307 lbs
Output Size	10-35 mm	0.4-1.4 inches
POWER UNIT		
Engine Type	4-cylinder water-cooled diesel engine	
Rated Power	26 kW	35 HP
Engine Speed	2400 RPM	
Start Method	Electric start	
Fuel Tank Capacity	30 L	7.9 US gal
CHIPPING SYSTEM		
Cutter Disc Diameter	560 mm	22.0 inches
Rotor Speed	1800 RPM	



TECHNICAL SPECIFICATIONS

Parameter	Metric	Imperial
Blade Configuration	4 moving blades + 2 fixed blades	
Disc Material	Hydraulic clutch + multi V-belt	
FEED SYSTEM		
Feed Method	Hydraulic auto feed, forward/reverse	
Feed Roller	Double hydraulic serrated rollers	
Feed Speed	0-30 m/min adjustable	
Feed Throat Size	460 × 400 mm	18.1×15.7 inches
DISCHARGE SYSTEM		
Discharge Chute	360° rotatable manual discharge chute	
Discharge Height	3200 mm	126.0 inches
Deflector	Manual adjustable deflector for direction control	
Throwing Height	7 m	23 ft
UNDERCARRIAGE		
Travel Method	Single axle towable	
Tire Specification	2pcs 15 inch heavy duty trailer tires	
Hitch	Adjustable height 2 inch ball hitch	
Support Jack	Foldable manual support jack	



TECHNICAL SPECIFICATIONS

SAFETY FEATURES

- Multiple emergency stop buttons
- Feed system safety interlock
- Full industrial safety guards
- Hydraulic system pressure protection
- Engine overheat/low oil protection

END PRODUCT & APPLICATIONS



Product Showcase



Typical Applications