



Model 6158 Track-Mounted Chain-Feed Wood Chipper

1-2 T/H CAPACITY | TOWABLE DIESEL BRANCH CHIPPER

APPLICATIONS

- Mountain forestry work
- Slope greening
- All terrain operation
- Steep slope chipping
- Remote forest access

KEY FEATURES

- 40HP diesel engine
- Rubber track, all terrain
- Chain auto feed, high efficiency
- Remote control walking
- 3-5T/H high capacity



TECHNICAL SPECIFICATIONS

Parameter	Metric	Imperial
GENERAL		
Capacity	3-5 T/H	3.3-5.5 ST/H
Max Processing Diameter	200 mm	7.9 inches
Overall Dimensions (L×W×H)	3200×1300×2000 mm	126.0×51.2×78.7 inches
Operating Weight	1200 kg	2646 lbs
Output Size	10-35 mm	0.4-1.4 inches
POWER UNIT		
Engine Type	V-twin 4-stroke air-cooled diesel engine	
Rated Power	29.4 kW	40 HP
Engine Speed	0-5 km/h	0-3.1 mph
Start Method	Electric start	
Fuel Tank Capacity	20 L	5.3 US gal
CHIPPING SYSTEM		
Rotor Speed	2000 RPM	
Blade Configuration	4pcs high alloy chipper blades + 1 bottom blade	
Drive System	Hydraulic clutch + multi V-belt	



TECHNICAL SPECIFICATIONS

Parameter	Metric	Imperial
FEED SYSTEM		
Feed Method	Chain conveyor hydraulic forced feed	
Feed Speed	0-25 m/min adjustable	
Feed Conveyor Length	1500 mm	59.1 inches
DISCHARGE SYSTEM		
Discharge Chute	360° rotatable high discharge	
Discharge Height	2800 mm	110.2 inches
Deflector	Hydraulic adjustable deflector	
UNDERCARRIAGE		
Travel Method	Rubber track self-propelled	
Track Width	230 mm	9.1 inches
Track Length	1200 mm	47.2 inches
Control Method	Wireless remote control	

SAFETY FEATURES

- Emergency stop button + remote emergency stop
- Feed system safety interlock
- Full cutting chamber guard
- Track travel safety lock
- Hydraulic system pressure protection
- Engine overheat/low oil protection

END PRODUCT & APPLICATIONS



Product Showcase



Typical Applications