



Model 654 Walk-behind Gasoline Sickle Mower

500-3000 m²/h | WALK-BEHIND GASOLINE SICKLE MOWER

APPLICATIONS

- Tall grass mowing
- Weed cutting
- Farmland edge weeding
- Wasteland mowing
- Alfalfa harvest

KEY FEATURES

- 6.5HP gasoline engine
- Reciprocating sickle bar cutter
- Self-propelled drive
- Clean low stubble cutting
- 800mm wide cutting path



TECHNICAL SPECIFICATIONS

Parameter	Metric	Imperial
GENERAL		
Working Efficiency	500-3000 m²/h	5380-32290 sq ft/h
Cutting Width	800 mm	31.5 inches
Overall Dimensions	1400×800×900 mm	55.1×31.5×35.4 inches
Net Weight	85 kg	187 lbs
Cutting Height	30-80 mm adjustable	1.2-3.1 inches adjustable
POWER UNIT		
Engine Type	4-stroke air-cooled gasoline engine	
Rated Power	4.8 kW	6.5 HP
Start Method	Recoil start	
Fuel Tank Capacity	3.6 L	1.0 US gal
Fuel Type	Unleaded gasoline	
CRUSHING SYSTEM		
Blade Type	Reciprocating sickle bar	
Blade Speed	1200 strokes/min	
Cutting Effec	Clean flat cut, low stubble	



TECHNICAL SPECIFICATIONS

Parameter	Metric	Imperial
TRAVEL SYSTEM		
Travel Method	Self-propelled walk-behind	
Wheel Specification	2pcs 12 inch rubber wheels	
Travel Speed	1-4 km/h	0.6-2.5 mph

SAFETY FEATURES

- Emergency stop lever
- Engine low oil protection
- Blade guard
- Handrail insulation protection

END PRODUCT & APPLICATIONS



Product Showcase



Typical Applications